



TABLE 1: CAPPING LAYER DEPTH
THE MINIMUM REQUIRED THICKNESS OF NON-FROST SUSCEPTIBLE CAPPING MATERIAL IS SHOWN HEREUNDER:

CBR SUBGRADE %	<2.5	3	4	5-15	>15
THICKNESS OF CAPPING LAYER(mm)	SPECIALIST GEOTECHNICAL ADVISE REQUIRED	350	300	250	150

CBR TEST SHALL BE CARRIED OUT AT A MINIMUM OF 60m INTERVALS

© ORDNANCE SURVEY IRELAND LICENSE No. AR 0062521.
ORDNANCE SURVEY IRELAND & GOVERNMENT OF IRELAND

File: 5150924_HTR_07_DS_0112.dwg
Date: Oct 08, 2021 - 4:12pm
Plotted by: yomacho

Rev	Description	By	Date	Chk'd	Auth
C	FOR PLANNING	YC	04.10.21	PF	KB
B	RFI	AK	28.07.21	KB	PF
A	FOR PLANNING	AK	24.02.21	JW	KB
-	FOR INFORMATION	AK	08.02.21	JW	KB



Atkins House, 150-155 Ainslie Business Park, Swords, Co. Dublin
Tel (+353) 01 810 8000
Fax (+353) 01 810 8001

Unit 2B, 2200 Cork Airport Business Park, Cork
Tel (+353) 021 429 0300
Fax (+353) 021 429 0360

1st Floor Technology House Parkmore Technology Park, Galway
Tel (+353) 061 786 050
Fax (+353) 061 776 830

Client		Purpose	
QUINTAIN DEVELOPMENTS IRELAND LTD		PLANNING	
Project		Title	
ADAMSTOWN DISTRICT CENTRE PHASE 2 - BLOCK G AMENDMENT		TYPICAL ROAD SECTIONS AND CONSTRUCTION DETAILS	
Original Scale	Design/Drawn	Checked	Authorised
N.T.S	AK	JW	KB
	Date: 08.02.21	Date: 08.02.21	Date: 08.02.21
Status	Drawing Number	Rev	
P	5150924 / HTR / 07 / DR / 0112	c	