

- THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER ARCHITECTURAL AND ENGINEERING DRAWINGS AND ALL OTHER RELEVANT DRAWINGS AND SPECIFICATIONS.
- DO NOT SCALE THIS DRAWING. USE FIGURED DIMENSIONS ONLY. • NO PART OF THIS DOCUMENT MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR STORED IN ANY RETRIEVAL SYSTEM OF ANY NATURE WITHOUT THE WRITTEN PERMISSION OF O'CONNOR SUTTON CRONIN AS COPYRIGHT HOLDER EXCEPT AS AGREED FOR USE ON THE PROJECT FOR WHICH THE DOCUMENT WAS ORIGINALLY ISSUED.

11.03.22	SUITABLE FOR STAGE APPROVAL.	I.F.	A.M.
31.02.22	SUITABLE FOR PLANNING	I.F.	A.M.
		31.02.22 SUITABLE FOR PLANNING	

Rev No.	Date	Revision Note	Drn by	Chkd by						d Office,
						ENVIRONMENT ISO 140012015		HEALTH & SAFETY ISO 450012018	Dubl	ussia Street lin 7. KT57
						NSAI Certif		NSAI Certified	TEL	+353 (0)1
						(BIM Desig Constructi Capital/De ISO 1965 VERIFIED	on livery I-1 and -2	e: w:	contactus www.ocs
									Dublir	n London E

DRAWING NOTES:

- 1. DUCTING SHALL COMPLY WITH BSEN 50086-1-2-3-4 LATEST EDITION & SHALL BE SINGLE WALL, COLOURED RED & MANUFACTURED FROM HIGH DENSITY POLYETHYLENE. THE NOMINAL EXTERNAL DIAMETER OF THE DUCT SHALL BE 107mm WITH A MINIMAL WALL THICKNESS OF 5mm. EACH LENGTH OF DUCT SHALL BE STAMPED WITH THE WORDS "PUBLIC LIGHTING", OR ALTERNATIVELY, "STREET LIGHTING", IN 18mm BLACK LETTERING AT 0 DEGREES, AT ONE METRE INTERVALS. DUCT SHALL BE LAID WITH THIS LEGEND FACING UPWARDS. DUCT SHALL BE LAID IN A STRAIGHT LINE CLOSE TO THE LINE OF THE COLUMN LOCATIONS & SHALL CONTAIN A CONTINUOUS DRAW WIRE OF 8KN STRENGTH.
- 2. A MINIMUM DEPTH OF 450mm COVER IS REQUIRED IN URBAN PATHWAYS & A MINIMUM OF 600mm COVER IS REQUIRED FOR GRASS MARGINS, PEDESTRIAN WAYS, LANEWAYS & GATEWAY ENTRANCES & A MINIMUM DEPTH OF 750mm IS REQUIRED AT ROAD CROSSINGS OR IN CARRIAGEWAYS.
- 3. ALL EQUIPMENT TO BE SUITABLY IP RATED FOR THE ENVIRONMENT THEY ARE BEING INSTALLED.
- 4. FOR SCHEDULES OF EQUIPMENT SEE SPECIFICATION.

5. THE COMPLETE INSTALLATION TO BE CO-ORDINATED WITH ALL OTHER SERVICES.

LEGEND OF SYMBOLS:

- 6 METER COLUMN MOUNTED 4000K LIGHT FITTING 6 METER COLUMN MOUNTED 3000K LIGHT FITTING PUBLIC LIGHTING MINI PILLAR
- MANHOLE/DRAWPIT
- PL _____ 110mm LV DUCT FOR PUBLIC LIGHTING



ELECTRICAL Title: PROPOSED SITE LIGHTING LAYOUT SITE PLAN

Belfast | Galway | Cork | Birmingham

Code Originator Zone Level Type Role Number	Status Revision
Code Originator Zone Level Type Role Number M1343 - OCSC - XX - XX - DR - E - 0002	S4 P02
Date: 22.12.21 Scale:1:500 @ A1 Drn by: C.T. Chkd by: A.	M. Aprvd by:M.F.