

Planning Department,  
South Dublin City Council,  
County Hall,  
Tallaght,  
Dublin 24

29<sup>th</sup> April 2022

SDCC Ref: SD21B/0529

Our Ref:22005\_Let\_SDCC\_220429

**RE: 60, BALLYROAN ROAD, TEMPLEOGUE, DUBLIN 16, D16V1Y6**

To whom it may Concern,

POGA Consulting Engineers were engaged to provide Engineering services at the above dwelling. On behalf of our client, we enclose our response to planning condition 2 issued as part of the final grant on 07/12/2021.

Planning condition 2 (A )states:

**(A) A report showing site specific soil percolation test results and design calculations for the proposed soakaway, which shall be in accordance with BRE Digest 365 - Soakaway Design.**

Our response is:

Trinity Green Environmental Consultants completed a site-specific Soil Infiltration Test for the purpose of designing a Soakaway, as part of this planning application. Please refer to Appendix A for the full Soil Infiltration Test Report. The soakaway tests were completed in accordance with BRE Digest 365, and the report concluded that the "soakage is slow and the watertable is high". Therefore, the soil was deemed unsuitable for infiltration and the alternative SuDS strategy of a Rainwater Garden was pursued.

The planter is designed to store the run off from 95% of the roof area for a 10 year storm event with a 2 hour duration - please refer to Appendix B for rainfall details and design of planter.

Planning condition 2(B) states:

(B) A revised drawing showing plan and cross-sectional views, dimensions, and location of proposed soakaway. Any proposed soakaway shall be located fully within the curtilage of the property and shall be:

- (i) At least 5m from any building, public sewer, road boundary or structure.
- (ii) Generally, not within 3m of the boundary of the adjoining property.
- (iii) Not in such a position that the ground below foundations is likely to be adversely affected.
- (iv) A minimum of 10m from any sewage treatment percolation area and from any watercourse/floodplain.
- (v) Soakaways shall include an overflow connection to the existing surface water drainage network.

Our response is:

The proposed Rainwater Garden planter is located to the rear of the dwelling. Please refer to Appendix C containing drawings 22005-100 and 22005-101, respectively, for the full surface water drainage layout and for a section through the proposed Rainwater Garden planter.

Planning condition 2(C) states:

(C) Water Butts shall be included as part of additional Sustainable Drainage Systems (SuDS) features.

Our response is:

The roof runoff will be directed to the Rainwater Garden planter through surface water pipes. On opposite sides of the roof, rain water butts will gather some of the roof rainwater and thus help to collect the runoff. Please refer to Appendix C containing drawings 22005-100 and 22005-101, respectively, for proposed rainwater butt locations and for typical rainwater butt connection to the dwelling's drainage network.

Planning condition 2(D) states:

(D) All works shall comply with the Building Regulations -Technical guidance document- Part H Drainage and Wastewater disposal.

Our response is:

All surface water drainage is designed in accordance with the Department of Environment Recommendation for Site Development Works, Building Regulations Part H (Drainage and Wastewater Disposal) and Irish Water Standards.

Planning condition 2(E) states:

(E) There shall be complete separation of the foul and surface water drainage for the proposed development.

REASON: In the interests of public health, the proper planning and sustainable development of the area and in order to ensure adequate surface water drainage provision.

Our response is:

Appendix D contains the Irish Water Utilities mapping for the drainage within the area. The mapping shows complete separation of existing foul and surface water networks in the region where the subject site is located. Furthermore, the foul and surface water connections from the existing network to the dwelling are also separate.

If you have any queries in relation to the above do not hesitate to contact me.

Yours sincerely



---

Eamonn Mahon *BEng(hons), MSc, CEng, MIEI, MIStructE*- Associate  
**On behalf of POGA Consulting Engineers**

## **APPENDIX A**

### SOIL INFILTRATION TEST

## Soil Infiltration Test for Design of Soakaway

At

60 Ballyroan Road

Prepared by

Dr. Eugene Bolton  
Senior Consultant  
Trinity Green

Report on Soil Infiltration Test

## *Introduction*

To manage the surface water from the development it is proposed to construct Soakaways in accordance with BRE Digest365 As part of this, the infiltration capacity of the soil was assessed. Dr. Eugene Bolton of Trinity Green Environmental Consultants was commissioned to carry out soil Infiltration Tests in accordance with BRE Digest365 to establish the suitability of the site for disposal of water.

### *1.0 Visual assessment of Site*

The site is located in an Urban setting where the sites are mature so there is no vegetation to indicate likely soakage properties of the soil. The landscape is relatively flat and on the day of the tests there was no surface water present.

### *Sub-soil profile*

A test pit was excavated to 0.95m bgl. There is a layer of black clayey topsoil to 300mm bgl. The subsoil to 800mm is a light brown CLAY lightly compacted. below this it a gravely SILT/CLAY but with low gravel content. Water was present at 850mm bgl

### *4.0 Infiltration Tests*

The Infiltration rate, generally expressed as metres per second, is the volume of water that enters the soil over a unit area and unit time. In order to obtain this measurement a pit is excavated and filled with water. The fall in the level of the water is recorded over time. a new test pit was opened that had dimensions

Length 1.2m

Width 0.3m

Depth 0.75m

.

The base of the pit was filled with water to a depth of 500mm and the drop in the water level was followed over time

### *5.0 Results*

The time required for the level to fall from 75% full to 25% full (ie 50% drop) – from a water depth of 0.375m to a water depth of 0.125m is estimated to be 987min.

Table 1 – Time taken for water level to fall

Elapsed Time (Mins)	Depth of Water (mm)
0	500
13	490
34	480
183	430
275	400
403	360
619	300
1219	150
1342	125

Infiltration rate (f) = Volume of water used/unit exposed area /unit time

$$\begin{aligned} \text{Volume} &= \text{pit length (m)} \times \text{Width (m)} \times \text{Drop in water level (m)} \\ &= 1.2 \times 0.3 \times 0.25 \\ &= 0.09\text{m}^3 \end{aligned}$$


$$\begin{aligned} \text{Exposed area} &= (\text{Length} \times \text{Half the effective height} \times 2) + (\text{Width} \times \text{Half the effective height} \times 2) + \text{Base area} \\ &= (1.2 \times 0.25 \times 2) + (0.3 \times 0.25 \times 2) + (1.2 \times 0.3) \\ &= 1.11\text{m}^2 \end{aligned}$$

Time = 987min

$$\begin{aligned} \text{Infiltration rate (f)} &= 0.09/1.11/987 \\ &= 8.2\text{E-}05 \text{ m/min} \\ \mathbf{f} &= \mathbf{1.3\text{E-}06 \text{ m/sec}} \end{aligned}$$

## 6.0 Conclusions

From the above observation it is concluded that the soakage is slow and watertable is high

Signed  .....

Dr. Eugene Bolton  
Senior Consultant  
Trinity Green

15/03/2022



**Photo**

Trial Pit – Depth 0.95 – water encountered at 0.85m bgl



Test Pit before water added – Depth 0.75m





Pit during test



## **APPENDIX B**

### **RAINFALL DATA & RAINGARDEN PLANTER DESIGN**

Met Eireann  
Return Period Rainfall Depths for sliding Durations  
Irish Grid: Easting: 312920, Northing: 227997,

DURATION	Interval		Years													
	6months,	1year,	2,	3,	4,	5,	10,	20,	30,	50,	75,	100,	150,	200,	250,	500,
5 mins	2.6,	3.9,	4.6,	5.6,	6.4,	6.9,	8.9,	11.1,	12.6,	14.8,	16.7,	18.2,	20.6,	22.5,	24.1,	N/A
10 mins	3.7,	5.4,	6.4,	7.8,	8.9,	9.7,	12.3,	15.5,	17.6,	20.6,	23.3,	25.4,	28.8,	31.4,	33.6,	N/A
15 mins	4.3,	6.3,	7.5,	9.2,	10.4,	11.4,	14.5,	18.2,	20.7,	24.2,	27.4,	29.9,	33.8,	36.9,	39.5,	N/A
30 mins	5.7,	8.3,	9.7,	11.9,	13.4,	14.6,	18.5,	23.0,	26.0,	30.4,	34.2,	37.3,	42.0,	45.7,	48.8,	N/A
1 hours	7.5,	10.9,	12.7,	15.4,	17.3,	18.7,	23.6,	29.1,	32.8,	38.1,	42.8,	46.5,	52.2,	56.7,	60.4,	N/A
2 hours	10.0,	14.2,	16.5,	19.9,	22.3,	24.1,	30.1,	36.9,	41.4,	47.8,	53.5,	58.0,	64.8,	70.2,	74.6,	N/A
3 hours	11.7,	16.6,	19.2,	23.1,	25.8,	27.9,	34.6,	42.3,	47.4,	54.6,	61.0,	66.0,	73.6,	79.6,	84.5,	N/A
4 hours	13.2,	18.6,	21.4,	25.7,	28.7,	30.9,	38.3,	46.7,	52.2,	60.0,	66.9,	72.3,	80.5,	87.0,	92.3,	N/A
6 hours	15.5,	21.7,	25.0,	29.9,	33.2,	35.8,	44.2,	53.6,	59.8,	68.5,	76.3,	82.2,	91.4,	98.6,	104.5,	N/A
9 hours	18.3,	25.4,	29.2,	34.8,	38.5,	41.5,	50.9,	61.6,	68.5,	78.3,	86.9,	93.6,	103.8,	111.7,	118.3,	N/A
12 hours	20.6,	28.4,	32.5,	38.7,	42.8,	46.0,	56.3,	67.9,	75.5,	86.0,	95.4,	102.6,	113.6,	122.1,	129.2,	N/A
18 hours	24.2,	33.2,	37.9,	45.0,	49.6,	53.3,	64.9,	78.0,	86.5,	98.3,	108.7,	116.7,	129.0,	138.5,	146.3,	N/A
24 hours	27.2,	37.1,	42.3,	50.0,	55.1,	59.1,	71.8,	86.0,	95.2,	108.0,	119.3,	128.0,	141.2,	151.4,	159.8,	188.9
2 days	34.1,	45.4,	51.3,	59.9,	65.5,	69.9,	83.7,	98.8,	108.6,	122.1,	133.8,	142.8,	156.4,	166.8,	175.4,	204.8
3 days	39.6,	52.1,	58.5,	67.8,	73.9,	78.5,	93.3,	109.3,	119.6,	133.7,	145.9,	155.2,	169.3,	180.1,	188.8,	218.9
4 days	44.5,	57.9,	64.8,	74.7,	81.2,	86.1,	101.6,	118.5,	129.2,	143.9,	156.5,	166.2,	180.7,	191.7,	200.7,	231.5
6 days	53.0,	68.1,	75.7,	86.7,	93.8,	99.2,	116.1,	134.3,	145.8,	161.5,	174.9,	185.1,	200.5,	212.1,	221.5,	253.6
8 days	60.6,	77.1,	85.3,	97.2,	104.8,	110.6,	128.7,	148.1,	160.2,	176.8,	190.9,	201.6,	217.7,	229.8,	239.6,	272.9
10 days	67.5,	85.2,	94.1,	106.7,	114.8,	121.0,	140.2,	160.5,	173.3,	190.6,	205.4,	216.5,	233.2,	245.7,	255.9,	290.3
12 days	74.0,	92.9,	102.2,	115.6,	124.1,	130.6,	150.7,	172.0,	185.3,	203.3,	218.7,	230.2,	247.4,	260.4,	270.9,	306.3
16 days	86.0,	106.9,	117.2,	131.8,	141.2,	148.2,	170.0,	192.9,	207.2,	226.5,	242.8,	255.1,	273.4,	287.1,	298.2,	335.4
20 days	97.1,	119.8,	131.0,	146.7,	156.8,	164.3,	187.6,	212.0,	227.1,	247.5,	264.7,	277.6,	296.8,	311.2,	322.8,	361.6
25 days	110.1,	134.9,	147.0,	164.0,	174.8,	183.0,	207.9,	233.9,	250.0,	271.6,	289.8,	303.5,	323.7,	338.8,	351.0,	391.6

NOTES:  
N/A Data not available  
These values are derived from a Depth Duration Frequency (DDF) Model  
For details refer to:  
'Fitzgerald D. L. (2007), Estimates of Point Rainfall Frequencies, Technical Note No. 61, Met Eireann, Dublin',  
Available for download at [www.met.ie/climate/dataproducts/Estimation-of-Point-Rainfall-Frequencies\\_TN61.pdf](http://www.met.ie/climate/dataproducts/Estimation-of-Point-Rainfall-Frequencies_TN61.pdf)


### Rainwater Garden Planter Design

<b>M10   120</b>	=	30.1	mm			
<b>Roof Area</b>	=	131	m <sup>3</sup>			
<b>Required Volume</b>	=	30.1	x	1.00E-03	x	131
<b>Required Volume</b>	=	3.94	m <sup>3</sup>			
<b>Void</b>	=	40%				
<b>Req. Volume Soil</b>	=	3.94	/	0.40	=	9.86 m <sup>3</sup>
<b>Planter Volume</b>	=	5	x	2	x	1
<b>Planter Volume</b>	=	10	m <sup>3</sup>			

## **APPENDIX C**

DRAWINGS 22005-100 & 22005-101





**DRAINAGE LAYOUT**  
Scale 1:150

- GENERAL**
1. Read in conjunction with all relevant Architect's and Engineer's drawings.
  2. Do not set out from this drawing. Setting out to be done from Architect's drawings.
  3. All houses to have individual 100mm diameter foul and surface water service connections.
  4. Adjust foundation depths as necessary to avoid being undermined by foul and surface water service connections.
  5. Where cover to pipes is less than 1.2m in roads, refer note 2 STD-WW-07. Surround to be in accordance with standard detail STD-WW-08. depth of cover to foul sewer pipes in accordance with standard detail STD-WW-07.
  6. Record drawings of the as constructed work shall be made available to POGA at the end of the project.
  7. All connections to existing foul and surface water must be determined by the main contractor prior to any construction on site. All existing invert levels to be confirmed to the engineers and all discrepancies notified to POGA before any construction commences.
  8. Pipe materials for the proposed gravity sewer and rising main shall be in compliance with Section 3.13 of the Wastewater Code of Practice.

- SURFACE WATER**
9. Surface Water manhole and road gully details to comply with Greater Dublin Regional Code of practice for Drainage Works.
  10. Please ensure that the external face of proposed manhole chambers are a minimum of 0.5m from kerb line and external face of sewers are a minimum of 1m from kerb line.
  11. All surface water pipes due to be taken in charge by the local authority to be S&S concrete with rubber rings. Twin-wall high density polyethylene pipes (up to 375mm dia.) may be acceptable. The contractor must confirm in writing twin-wall pipes are acceptable to the Local Authority before use.
  12. Bedding and surround as per Greater Dublin Regional Code of Practice for Drainage Works
  13. Manhole covers and frames shall comply with the LA standard pattern with min opening of 675mm & with closed keyways. All Manholes covers to comply with IS EN 124:1994. Group 4 (min. class D400) manholes in all trafficked areas. Minimum Group 2 (min. class B125) to be used in footways, pedestrian areas and comparable areas. Class D400 should be used in footpaths where heavy vehicles have the potential to access or mount footpaths and these covers should be free of trip hazards, removable parts and be lockable Group 1 (min. class A15) may be used in enclosed private gardens only.
  14. Manholes on house drains to be in private property. House drains shall not pass through property they do not serve.
  15. Double gullies, with separate connections to main, to be provided at low points and at the ends of Cul de Sacs. Maximum run of pipe 15m. Minimum pipe diameter 150mm. Maximum gully spacing for roads up to 7m wide to be 50m UNG. All Road gullies to be closed in the direction of traffic flow.
  16. All gully tops shall comply with the LA standard: Group 3 (min. class C250) where gully are located in the kerbside channels of roads which when measured from the kerb, extend a maximum of 0.5m into the carriageway and a maximum of 0.2m into the footway, Group 4 (min Class D400) to be used elsewhere. All gully covers to comply with IS EN 124:1994.
  17. No ponding is acceptable. All levels to be dish to gullies.
  18. Final connections to be made by Irish Water or agents acting on their behalf. Connections are not to be made by the contractor without Irish Water written agreement in place.

- FOUL**
19. There are summary notes, refer to Irish Wastewater Code of Practice and Standard Details for full notes and details. Where discrepancy between these and Irish Water publication are identified, Irish Water publications take precedence. All discrepancies should be reported to POGA.
  20. All foul manholes to comply with Irish Wastewater standard details.
  21. Please ensure that the external face of proposed manhole chambers (not cover) are a minimum of 0.5m from kerb line and external face of sewers are a minimum of 1m from kerb line.
  22. All foul pipes due to be taken in charge by the Irish Wastewater Code of Practice to be S&S concrete with rubber rings or Wavin OSMA UltraRib with a stiffness classification of SN8. 8. Pipe materials for the proposed gravity sewer and rising main shall be in compliance with Section 3.13 of the Wastewater Code of Practice. Backfill and bedding shall comply with Irish Water Standard Detail STD-WW-07 Concrete bed, haunch and surround to wastewater pipes shall comply with standard detail STD-WW-08.
  23. Where cover to pipes is less than 1.2m in roads, 0.9m in public areas where access is limited to a gross weight of 7.5 tonne vehicles, and 0.8m in grassed/landscaped areas, surround the pipe in 150mm concrete to IW detail STD-WW-08. Absolute Minimum Cover above the external crown of the pipe of 750mm.
  24. All foundations to be taken below sewer depths.
  25. Manhole covers and frames shall comply with the Irish Wastewater Code of Practice standard pattern with min opening of 600mm & with closed keyways. All Manholes covers to be circular and comply with IS EN 124:1994. Group 4 (min. class D400) manholes in all trafficked areas, Minimum Group 2 (min. class B125) to be used in footways, pedestrian areas and comparable areas, Class D400 should be used in footpaths where heavy vehicles have the potential to access or mount footpaths and these covers should be free of trip hazards, removable parts and be lockable.
  26. From finished ground level to the first step shall be a maximum of 675mm. Stainless Steel ladder to be provide where depth of manhole exceeds 3m.
  27. Manholes and inspection chambers on house drains to be in private property. Provide inspection chambers on individual service connections within 1m of the boundary. See section 3.11.13 of Wastewater Code of Practice and STD-WW-03 of Wastewater Infrastructure Standard Details.
  28. Final connections to be made by the Local Authority as agents acting for Irish Water. Connections are not to be made by the contractor without the Irish Water written agreement in advance.

Please refer to the most up to date Irish Water (IW) documents, IW-CDS-5030-01 for Wastewater Infrastructure Standard Details. These details superseded all previously issued POGA wastewater details and should be used on all new and part constructed developments from the December 2017.

Drawing No.	Drawing Title	Rev
STD-WW-01	Waste water service connection responsibility	1
STD-WW-02	Typical layout for sewer within new developments	1
STD-WW-03	Drain & service connection pipework	1
STD-WW-04	Typical sewer / service pipe connection	1
STD-WW-05	Typical service layout indicating separation distances	1
STD-WW-06	Restrictions on wastewater infrastructure adjacent to trees	1
STD-WW-06A	Restrictions on trees/shrubs planting adjacent to sewers	2
STD-WW-07	Trench backfill & bedding	0
STD-WW-08	Concrete bed, haunch & surround to wastewater pipes	0
STD-WW-09	Blockwork manhole (<450mm dia.)	2
STD-WW-10	Pre-cast concrete manhole	2
STD-WW-11	In-situ concrete manhole	2
STD-WW-12	Backdrop manholes	2
STD-WW-13	Private side inspection chamber	2
STD-WW-14	Thrust blocks for rising mains	1
STD-WW-15	Scour valve chamber (foul rising main <200mm dia.)	2
STD-WW-16	Sluice valve details for rising mains ductile iron (D.I.) pipe (<200mm dia.) (sheet 1 of 2)	3
STD-WW-17	Sluice valve details for rising mains polyethylene (P.E.) pipe (<200mm dia.) (sheet 2 of 2)	2
STD-WW-18	Air valve chamber (foul rising main <200mm dia.)	2
STD-WW-19	Duct chamber	1
STD-WW-20	Emergency overflow structure	2
STD-WW-21	Typical ditch/stream crossing for gravity main (sheet 1 of 2)	1
STD-WW-22	Typical ditch/stream crossing for rising main (sheet 2 of 2)	1
STD-WW-23	Typical bridge crossing for rising main (sheet 1 of 2)	1
STD-WW-24	Typical bridge crossing for rising main (sheet 2 of 2)	1
STD-WW-25	Security gate & fencing	2
STD-WW-26	Indicative pumping station layout	0
STD-WW-27	Flow meter chamber (foul rising main <200mm dia.)	2
STD-WW-28	Indicative submersible pumping station	2
STD-WW-28A	Indicative pre-cast concrete submersible pumping station	1
STD-WW-29	Rising main discharge manhole	2
STD-WW-30	Kiosk type 1 pumping station & wet kiosk (sheet 1 of 2)	2
STD-WW-31	Kiosk type 2 + 3 pumping station & wet kiosk (sheet 2 of 2)	2
STD-WW-32	Handstanding area pumping station (permeable & impermeable)	1
STD-WW-33	Lamp bollard & lamp standard	1
STD-WW-34	Vent stack	1

The above applied to wastewater only, refer to POGA Standard Details for Surface Water infrastructure.

**DRAINAGE LEGEND**

- SITE BOUNDARY
- Existing SW Sewer
- Existing FW Sewer
- RWB ● PROPOSED RAINWATER BUTT
- PROPOSED Ø100mm HOUSE DRAINS AT 1:80 min. GRADIENT WITH INSPECTION CHAMBERS (STD-WW-03)
- AJ ■ ACCESS JUNCTION
- RGP ■ PROPOSED RAIN GARDEN PLATER
- ROOF AREA
- FFL 63.500 ■ PROPOSED FINISHED FLOOR LEVEL

© This drawing is Copyright and must only be used for the project named. Ordnance Survey Ireland Licence No. EN 0055638 © Ordnance Survey Ireland / Government of Ireland

PO	Date	Description	AC
29/04/2022	ISSUED FOR PLANNING		AC

Project Title  
**EXTENSION & ALTERATIONS AT 60 BALLYROAN ROAD, CO. DUBLIN**

Architect  
**JOE FALLON DESIGN ARCHITECTURE**

Date	By	Checked	Scale @ A1
APRIL 2022	AC	EM	1:150

Drawing Title  
**DRAINAGE LAYOUT**

Drawing Status  
**PLANNING**

Job No.	Drawing No.	Issue
22005	100	PO

**POGA**  
CONSULTING ENGINEERS  
STRUCTURAL • CIVIL


Unit C2, Nutgrove Office Park  
Rathfarnham  
Dublin 14  
D14 CR20  
Tel +353 (0)1 205 1101  
www.poga.ie



- GENERAL**
1. Read in conjunction with all relevant Architect's and Engineer's drawings.
  2. Do not set out from this drawing. Setting out to be done from Architect's drawings.
  3. Adjust foundation depths as necessary to avoid being undermined by foul and surface water service connections.
  4. Where cover to pipes is less than 1.2m in roads, refer note 2 STD-WW-07. Surround to be in accordance with standard detail STD-WW-08, depth of cover to foul sewer pipes in accordance with standard detail STD-WW-07.
  5. Record drawings of the as constructed work shall be made available to POGA at the end of the project.
  6. All connections to existing foul and surface water must be determined by the main contractor prior to any construction on site. All existing invert levels to be confirmed to the engineers and all discrepancies notified to POGA before any construction commences.
  7. Pipe materials for the proposed gravity sewer and rising main shall be in compliance with Section 3.13 of the Wastewater Code of Practice.



**RAINWATER BUTT CONNECTION**  
NTS



**Section - Rain Garden Planter**  
Scale 1:20

Rev.	Date	Description	By
PO	29/04/2022	ISSUED FOR PLANNING	AC

Project Title  
**EXTENSION & ALTERATIONS AT 60 BALLYROAN ROAD, CO. DUBLIN**

Architect  
**JOE FALLON DESIGN ARCHITECTURE**

Date	By	Checked	Scale @ A2
APRIL 2022	AC	EM	AS SHOWN

Drawing Title  
**SUDS & DRAINAGE DETAILS**

Drawing Status  
**PLANNING**

Job No.	Drawing No.	Issue
22005	101	PO

**POGA**  
CONSULTING ENGINEERS  
STRUCTURAL + CIVIL

Unit C2, Nutgrove Office Park  
Rathfarnham  
Dublin 14  
D14 CR20  
Tel +353 (0)1 205 1101  
www.poga.ie

## **APPENDIX D**

### **IRISH WATER EXISTING DRAINAGE MAPPING**




# Irish Water Web Map



Print Date: 20/04/2022

Printed by: Irish Water



1. No part of this drawing may be reproduced or transmitted in any form or stored in any retrieval system of any nature without the written permission of Irish Water's copyright holder except as agreed for use on the project for which the document was originally issued.

2. Whilst every care has been taken in its compilation, Irish Water gives this information as to the position of its underground network as a general guide only on the strict understanding that it is based on the best available information provided by each Local Authority in Ireland to Irish Water. Irish Water can assume no responsibility for and give no guarantees, undertakings or warranties concerning the accuracy, completeness or up to date nature of the information provided and does not accept any liability whatsoever arising from any errors or omissions. This information should not be relied upon in the event of excavations or any other works being carried out in the vicinity of the Irish Water underground network. The onus is on the parties carrying out excavations or any other works to ensure the exact location of the Irish Water underground network is identified prior to excavations or any other works being carried out. Service connection pipes are not generally shown but their presence should be anticipated.

© Copyright Irish Water  
 Reproduced from the Ordnance Survey Of Ireland by Permission of the Government.  
 License No. 3-3-34

\*Gas Networks Ireland (GNI), their affiliates and assigns, accept no responsibility for any information contained in this document concerning location and technical designation of the gas distribution and transmission network ("the Information"). Any representations and warranties express or implied, are excluded to the fullest extent permitted by law. No liability shall be accepted for any loss or damage including, without limitation, direct, indirect, special, incidental, punitive or consequential loss including loss of profits, arising out of or in connection with the use of the information (including maps or mapping data).

NOTE: DIAL BEFORE YOU DIG Phone: 1850 427 747 or e-mail dig@gasnetworks.ie - The actual position of the gas/electricity distribution and transmission network must be verified on site before any mechanical excavating takes place. If any mechanical excavation is proposed, hard copy maps must be requested from GNI re gas. All work in the vicinity of gas distribution and transmission network must be completed in accordance with the current edition of the Health & Safety Authority publication, 'Code of Practice For Avoiding Danger From Underground Services' which is available from the Health and Safety Authority (1890 28 93 89) or can be downloaded free of charge at [www.hsa.ie](http://www.hsa.ie)."

<b>Water Distribution Network</b> Water Treatment Plant Water Pump Station Storage Cell/Tower Dosing Point Meter Station Abstraction Point Telemetry Kiosk <b>Reservoir</b> Potable Raw Water <b>Water Distribution Mains</b> Irish Water Private <b>Trunk Water Mains</b> Irish Water Private <b>Water Lateral Lines</b> Irish Water Non IW Water Casings Water Abandoned Lines Boundary Meter Bulk/Check Meter Group Scheme Source Meter Waste Meter Unknown Meter; Other Meter Non-Return PRV PSV Sluice Line Valve Open/Closed Butterfly Line Valve Open/Closed Sluice Boundary Valve Open/Closed Butterfly Boundary Valve Open/Closed Scour Valves Single Air Control Valve Double Air Control Valve Water Stop Valves Water Service Connections Water Distribution Chambers Water Network Junctions Pressure Monitoring Point Fire Hydrant Fire Hydrant/Washout <b>Water Fittings</b> Cap Reducer Tap Other Fittings	<b>Sewer Foul Combined Network</b> Waste Water Treatment Plant Waste Water Pump station <b>Sewer Mains Irish Water</b> Gravity - Combined Gravity - Foul Gravity - Unknown Pumping - Combined Pumping - Foul Pumping - Unknown Syphon - Combined Syphon - Foul Overflow <b>Sewer Mains Private</b> Gravity - Combined Gravity - Foul Gravity - Unknown Pumping - Combined Pumping - Foul Pumping - Unknown Syphon - Combined Syphon - Foul Overflow Sewer Lateral Lines Sewer Casings <b>Sewer Manholes</b> Standard Backdrop Cascade Catchpit Bifurcation Hatchbox Lamphole Hydrobrake Other; Unknown <b>Discharge Type</b> Outfall Overflow Soakaway Other; Unknown <b>Gas Networks Ireland</b> Transmission High Pressure Gasline Distribution Medium Pressure Gasline Distribution Low Pressure Gasline <b>ESB Networks</b> <b>ESB HV Lines</b> HV Underground HV Overhead HV Abandoned <b>ESB MV/LV Lines</b> MV Overhead Three Phase MV Overhead Single Phase LV Overhead Three Phase LV Overhead Single Phase MVLV Underground Abandoned <b>Non-Service Categories</b> Proposed Under Construction Out of Service Decommissioned <b>Water Non-Service Assets</b> Water Point Feature Water Pipe Water Structure <b>Water Non-Service Assets</b> Waste Point Feature Sewer Waste Structure	<b>Storm Water Network</b> <b>Surface Water Mains</b> Surface Gravity Mains Surface Gravity Mains Private Surface Water Pressurised Mains Surface Water Pressurised Mains Private <b>Inlet Type</b> Gully Standard Other; Unknown <b>Storm Manholes</b> Standard Backdrop Cascade Catchpit Bifurcation Hatchbox Lamphole Hydrobrake Other; Unknown Storm Culverts Storm Clean Outs Stormwater Chambers <b>Discharge Type</b> Outfall Overflow Soakaway Other; Unknown <b>Gas Networks Ireland</b> Transmission High Pressure Gasline Distribution Medium Pressure Gasline Distribution Low Pressure Gasline <b>ESB Networks</b> <b>ESB HV Lines</b> HV Underground HV Overhead HV Abandoned <b>ESB MV/LV Lines</b> MV Overhead Three Phase MV Overhead Single Phase LV Overhead Three Phase LV Overhead Single Phase MVLV Underground Abandoned <b>Non-Service Categories</b> Proposed Under Construction Out of Service Decommissioned <b>Water Non-Service Assets</b> Water Point Feature Water Pipe Water Structure <b>Water Non-Service Assets</b> Waste Point Feature Sewer Waste Structure
---	--	--

