



**PercolationTests.ie**  
Planning Assessments & Land Surveys

Tel: 087 6636 757    Email: [percolationtests@gmail.com](mailto:percolationtests@gmail.com)    Web: [www.percolationtests.ie](http://www.percolationtests.ie)

# **BRE Digest 365 Report.**

Prepared on behalf of:

**Ailish Russell**

At:

**31 Templeville Road,  
Dublin 6W.**

**Cilron Limited**  
 Newtownmoyaghy, Killock, Co Kildare.  
 www.perculationtests.ie  
 Tel: 087 6636757

**BRE Digest 365 Test**

Revision: 1.00

Job No: Soakpit 1 Page: C/01

Section: 31 Templeville Road, Dublin 6W

Prepared By: DR Date: 29/06/2022

ALTERNATIVE SOAKAWAY SIZES			
	trench soakaways		
	450	600	900
width of trench [mm]			
required trench length [m]	11.28	9.05	6.57
	ring soakaways		
	1500	2100	2400
diameter of ring [mm]			
required pit diameter [m]	2.35	2.35	2.35

\* Based on effective depth and number of pits as in Soakaway Data table

SUMMARY OF CALCULATIONS	
critical design rainfall duration 't <sub>crit</sub> '	= 240 min
required storage volume 'V <sub>req</sub> '	= 2.33 m <sup>3</sup>
provided storage volume 'V <sub>prov</sub> '	= 2.57 m <sup>3</sup>
utilisation factor	= 0.91 .OK
required time to discharge 50% 't <sub>50</sub> '	= 4.63 hours
utilisation factor	= 0.19 .OK

GENERAL DATA	
site location:	Ireland
soakaway type:	Infilled pit or trench
impermeable area drained to soakaway 'A' [m <sup>2</sup> ]	= 77
60 min rainfall depth of 5 year return period 'R' [mm]	= 16
M5-60 to M5-2d rainfall ratio 'r'	= 0.28
allowance for climate change:	20%

SOAKAWAY DATA	
soakaway width 'W' [m]	= 1.50
soakaway length 'L' [m]	= 4.50
total depth from ground level 'D <sub>g</sub> ' [m]	= 1.00
depth to drain invert level 'D <sub>d</sub> ' [m]	= 0.60
soakaway effective depth 'D <sub>eff</sub> ' [m]	= 0.40
free volume in infill aggregate [%]	= 95

SOIL INFILTRATION DATA	
allowance for infiltration through soakaway base:	30%
available on-site infiltration test results:	<input checked="" type="radio"/> Yes <input type="radio"/> No
use soakage trial pit table below	
internal surface area of trial pit 'a <sub>ps0</sub> ' [m <sup>2</sup> ]	= 1.25
storage volume between 75-25% 'V <sub>p</sub> ' [m <sup>3</sup> ]	= 0.13
time for water to fall from 75-25% 't <sub>p</sub> ' [min]	= 95.83
soil infiltration rate 'r' [m/s]	= 1.74E-05

SOAKAGE TRIAL PIT DATA	
soakage trial pit width 'W <sub>i</sub> ' [m]	= 0.50
soakage trial pit length 'L <sub>i</sub> ' [m]	= 1.00
total depth from ground level 'D <sub>gb</sub> ' [m]	= 1.20
depth to pipe invert level 'D <sub>ip</sub> ' [m]	= 0.70
soakage trial pit effective depth 'D <sub>iet</sub> ' [m]	= 0.50
free volume in infill aggregate [%]	= 100

NOTE: faces of excavation assumed to be vertical


**Infiltration Rate: Good - No Winter high watertable noted above 1.2m below ground**

REQUIRED STORAGE CAPACITY PER RAINFALL DURATION													
rainfall duration [min]	rainfall factor Z1	M5-D rainfalls [mm]	M30-D			Ignore			Ignore			outflow from soakaway [m <sup>3</sup> ]	required storage [m <sup>3</sup> ]
			Z2	rainfalls [mm]	inflow [m <sup>3</sup> ]	Z2	rainfalls [mm]	inflow [m <sup>3</sup> ]	Z2	rainfalls [mm]	inflow [m <sup>3</sup> ]		
5	0.33	5.21	1.44	9.02	0.69						0.02	0.67	
10	0.48	7.57	1.47	13.31	1.02						0.05	0.98	
15	0.58	9.14	1.48	16.24	1.25						0.07	1.18	
30	0.76	11.96	1.49	21.41	1.65						0.14	1.51	
60	1.00	15.70	1.49	28.06	2.16						0.28	1.89	
120	1.27	19.88	1.47	35.15	2.71						0.55	2.15	
240	1.63	25.53	1.46	44.67	3.44						1.11	2.33	
360	1.86	29.20	1.45	50.67	3.90						1.66	2.24	
600	2.22	34.79	1.43	59.66	4.59						2.77	1.82	
1440	3.05	47.65	1.38	79.36	6.11						6.65	0.00	

\* Z2 is a growth factor from M5 rainfalls

SOAKAGE TRIAL PIT INFILTRATION TEST RESULTS																				
water level measurement N <sup>o</sup>		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
Soakage Trial 1	time [min] =	0	90																	
	depth to water [m] =	0.80	1.10																	
Soakage Trial 2	time [min] =	0	95																	
	depth to water [m] =	0.80	1.10																	
Soakage Trial 3	time [min] =	0	115																	
	depth to water [m] =	0.80	1.10																	

# TEMPLEVILLE ROAD



POSED SITE PLAN 1:500



CONTIGUOUS REAR ELEVATION 1:200

ITERATIONS + ADDITIONS TO 31 TEMPLEVILLE ROAD.  
 + AILISH RUSSELL  
 EVAN MRSI ARCHITECT  
 > PLAN & DESIGN <

# The best in stormwater solutions made better still

AquaCell systems are the tried, tested and fully BBA approved answer to the effective management of excessive rainfall, whether through attenuation or infiltration solutions.

Now refined to offer three crate variants, the entire range is engineered from reformulated, recycled material for outstanding sustainable performance in every application.

As concern grows over the effects of climate change and the challenges of increasing urbanisation, AquaCell continues to rain supreme as the cost-effective, proven and versatile stormwater solution.



Discover more online at:  
[aquacell.wavin.co.uk](http://aquacell.wavin.co.uk)

# Storming ahead – from roof to river

From infiltration and attenuation units to advanced siphonic rainwater systems, vortex valves and drainage solutions, Wavin leads the way in stormwater management.



Wavin is part of Orbia, a community of companies working together to tackle some of the world's most complex challenges. We are bound by a common purpose: To Advance Life Around the World.

Wavin Limited  
Registered Office | Edlington Lane | Doncaster | DN12 1BY  
Tel. 0844 856 5152 | [www.wavin.co.uk](http://www.wavin.co.uk) | [Info@wavin.co.uk](mailto:Info@wavin.co.uk)

Met Eireann  
Return Period Rainfall Depths for sliding Durations  
Irish Grid: Easting: 319075, Northing: 232626,

DURATION	Years														
	Interval	2,	3,	4,	5,	10,	20,	30,	50,	75,	100,	150,	200,	250,	500,
5 mins	2.6,	4.2,	5.1,	5.7,	6.2,	7.8,	9.6,	10.7,	12.4,	13.9,	15.1,	16.8,	18.2,	19.4,	N/A,
10 mins	3.6,	5.9,	7.2,	8.0,	8.7,	10.8,	13.3,	15.0,	17.3,	19.4,	21.0,	23.5,	25.4,	27.0,	N/A,
15 mins	4.2,	7.0,	8.4,	9.4,	10.2,	12.7,	15.7,	17.6,	20.3,	22.8,	24.7,	27.6,	29.9,	31.8,	N/A,
30 mins	5.6,	9.0,	10.8,	12.1,	13.0,	16.2,	19.7,	22.0,	25.3,	28.2,	30.5,	34.0,	36.7,	38.9,	N/A,
1 hours	7.3,	11.7,	14.0,	15.5,	16.7,	20.5,	24.8,	27.6,	31.5,	35.0,	37.7,	41.8,	45.0,	47.7,	N/A,
2 hours	9.7,	15.2,	18.0,	19.9,	21.3,	26.0,	31.2,	34.5,	39.3,	43.4,	46.6,	51.5,	55.3,	58.4,	N/A,
3 hours	11.4,	17.7,	20.8,	23.0,	24.6,	29.8,	35.6,	39.4,	44.6,	49.3,	52.8,	58.2,	62.3,	65.7,	N/A,
4 hours	12.8,	19.7,	23.2,	25.5,	27.2,	32.9,	39.2,	43.3,	48.9,	53.9,	57.6,	63.4,	67.9,	71.5,	N/A,
6 hours	15.1,	22.9,	26.8,	29.4,	31.4,	37.8,	44.8,	49.3,	55.6,	61.1,	65.3,	71.6,	76.5,	80.5,	N/A,
9 hours	17.8,	26.7,	31.1,	34.0,	36.3,	43.4,	51.2,	56.3,	63.2,	69.3,	73.9,	80.9,	86.2,	90.6,	N/A,
12 hours	20.0,	29.7,	34.6,	37.7,	40.2,	47.9,	56.4,	61.8,	69.3,	75.7,	80.7,	88.2,	93.9,	98.6,	N/A,
18 hours	23.5,	34.6,	40.1,	43.6,	46.4,	55.0,	64.5,	70.5,	78.7,	85.9,	91.3,	99.6,	105.9,	111.0,	N/A,
24 hours	26.4,	38.5,	44.5,	48.4,	51.4,	60.7,	70.9,	77.4,	86.2,	93.9,	99.8,	108.6,	115.3,	120.7,	139.4,
2 days	32.1,	45.6,	52.1,	56.3,	59.5,	69.5,	80.2,	87.0,	96.2,	104.2,	110.1,	119.1,	125.9,	131.5,	150.2,
3 days	36.7,	51.3,	58.3,	62.8,	66.2,	76.7,	88.0,	95.1,	104.7,	112.9,	119.1,	128.3,	135.3,	141.0,	160.2,
4 days	40.7,	56.3,	63.7,	68.4,	72.0,	83.1,	94.8,	102.2,	112.1,	120.6,	127.0,	136.5,	143.7,	149.5,	169.1,
6 days	47.8,	65.0,	73.0,	78.2,	82.1,	94.1,	106.7,	114.5,	125.1,	134.1,	140.8,	150.8,	158.4,	164.5,	184.9,
8 days	54.0,	72.6,	81.2,	86.8,	90.9,	103.7,	117.0,	125.3,	136.4,	145.8,	152.9,	163.4,	171.2,	177.5,	198.7,
10 days	59.6,	79.5,	88.7,	94.5,	98.9,	112.4,	126.4,	135.0,	146.7,	156.5,	163.8,	174.7,	182.8,	189.4,	211.2,
12 days	64.9,	86.0,	95.6,	101.7,	106.3,	120.4,	135.0,	144.0,	156.1,	166.3,	173.9,	185.1,	193.5,	200.3,	222.8,
16 days	74.7,	97.8,	108.3,	114.9,	119.9,	135.1,	150.8,	160.4,	173.3,	184.2,	192.2,	204.1,	213.0,	220.1,	243.8,
20 days	83.7,	108.6,	119.9,	127.0,	132.3,	148.5,	165.1,	175.3,	188.9,	200.3,	208.8,	221.3,	230.6,	238.1,	262.9,
25 days	94.2,	121.2,	133.3,	140.9,	146.6,	163.9,	181.6,	192.5,	206.9,	218.9,	227.9,	241.1,	250.8,	258.7,	284.6,

NOTES:

N/A Data not available  
These values are derived from a Depth Duration Frequency (DDF) Model  
For details refer to:  
'Eitzgerald D. L. (2007), Estimates of Point Rainfall Frequencies, Technical Note No. 61, Met Eireann, Dublin',  
Available for download at [www.met.ie/climate/dataproducts/Estimation-of-Point-Rainfall-Frequencies\\_TN61.pdf](http://www.met.ie/climate/dataproducts/Estimation-of-Point-Rainfall-Frequencies_TN61.pdf)



# PercolationTests.ie

Planning Assessments & Land Surveys

Tel: 087 6636 757 Email: [percolationtests@gmail.com](mailto:percolationtests@gmail.com) Web: [www.percolationtests.ie](http://www.percolationtests.ie)



BRE digest 365 test hole

31 Templeville Road -  
29/06/2022



You're safe with *Sound*.

David Ryan  
Cillron Limited  
Newtownmoyaghy  
Kilcock  
Co Meath

Sound Insurance  
Unit 7 Burnell Court  
Northern Cross  
Malahide Road  
Dublin 17

E: [emailus@sound.ie](mailto:emailus@sound.ie)  
T: +353 1 524 2800

[sound.ie](http://sound.ie)

Date: 22/03/2022  
Reference: RYDA01001

### INSURANCE CERTIFICATE

To Whom It May Concern

We confirm we act as Insurance Brokers to the above and set out below a summary of cover we have arranged:

**Business Description:** *Soil Engineer (Percolation Testing)*

#### PROFESSIONAL INDEMNITY

<b>Policy No.</b>	PID00024862
<b>Insurer:</b>	Accredited Insurance (Europe) Ltd
<b>Period of Insurance:</b>	04/03/2022 to 03/03/2023
<b>Limit of Indemnity:</b>	€1,000,000

*Subject always to Insurers policy wording, warranties, conditions, restrictions & exclusions a copy of which is available on request.*


We trust this is in order but if you have any queries, please do not hesitate to contact us.

Yours sincerely,




Gary Kinsella  
Commercial Broker  
P: (01) 524 1415  
E: [Gary@sound.ie](mailto:Gary@sound.ie)







## AquaCell ECO

ECO is manufactured from specially reformulated, recycled material and has been designed for shallow, non-trafficked, landscaped applications.





## AquaCell CORE-R

CORE-R has been designed for use in deep applications, subject to both regular and heavy traffic loadings, such as cars and HGV's.



## AquaCell PLUS-R


PLUS-R has been designed primarily for use in applications where inspection is required, and is suitable for use in all applications from landscaped areas to heavily trafficked areas.



# AquaCell

Re-engineered to rain  
supreme for years to come

The new AquaCell range engineered  
from reformulated, recycled material.



**wavin**