Tel: 087 6636 757 Email: percolationtests@gmail.com Web: www.percolationtests.ie

BRE Digest 365 Report.

Prepared on behalf of:

John Lyons

At:

51 Grange Park & St Patricks
Cottages,
Rathfarnham,
Dublin.

Tel: 087 6636 757 Email: percolationtests@gmail.com Web: www.percolationtests.ie

Scope of Report.

The findings of this report are the result of an on-site infiltration test. Interpretations and conclusions included in the report are based on knowledge of the ground conditions following detailed investigations, as well as the regional soils, subsoils and bedrock geology, and the experience of the author. David Ryan has prepared this report in line with the best current practice and with all reasonable skill, care and diligence in consideration of the limits imposed by the survey techniques used and resources devoted to it by agreement with the client.

David Ryan accepts no responsibility for any matters arising if any recommendations contained in this document are not carried out, or are partially carried out, without further advice being obtained from David Ryan.

ALTERNATIVE SOAKAWAY SIZES										
	trer	ays								
width of trench [mm]:	450	900								
required trench length [m]:	5.24	4.19	3.07							
	ring soakaways									
diameter of ring [mm]:	1500	2100	2400							
required pit diameter [m]:	1.60	1.61	1.60							

^{*}Based on effective depth and number of pits as in Soakavay Data table

SUMMARY OF CALCULATIONS										
critical design rainfall duration tora' =	240	min								
required storage volume 'V _{req} ' =	2.21	m³								
provided storage volume 'Vprov' =	2.28	m³								
utilisation factor =	0.97	.oĸ								
required time to discharge 50% 150' =	4.00	hours								
utilisation factor =	0.17	.oĸ								

GENERAL DATA						
site location: Ireland						
soakaway type: infilled pit or trench						
impermeable area drained to scakaway 'A' $[m^2] =$	75					
60 min rainfall depth of 5 year return period 'R' [mm] =	16					
M5-60 to M5-2d rainfall ratio 'r' =	0.28					
allowance for climate change:	20%					

SOIL INFILTRATION DATA								
allowance for infiltration through soakaway base:	20%							
available on-site infiltration test results: <a> Yes	○ No							
use soakage trial pit table below								
internal surface area of trial pit 'ap50' [m2] =	1.10							
storage volume between 75-25% 'Vp' [m³] =	0.10							
time for water to fall from 75-25% tp' [min] =	65.00							
soil infiltration rate 4 [m/s] = 2	.33E-05							

SOAKAWAY DATA	
soakaway width 'W' [m] =	1.50
soakaway length 'L' [m] ≕	2.00
total depth from ground level 'D _b ' $[m]$ =	1.20
depth to drain invert level 'D _d ' [m] =	0.40
soakaway effective depth 'D _{eff} ' [m] =	0.80
free volume in infill aggregate [%] =	95

SOAKAGE TRIAL PIT DATA	
scakage trial pit width 'Wt' [m] =	0.50
soakage trial pit length 'L _! ' [m] =	1.00
total depth from ground level 'Dtb' [m] =	1.20
depth to pipe invert level 'D _{tp} ' [m] =	0.80
soakage trial pit effective depth 'Dteff' [m] =	0.40
free volume in infill aggregate [%] =	100
NOTE: faces of excavation assumed t	o be vertical

Infiltration rate: Very good – No mottling noted above 1.2m below ground level.

	SOAKAGE TRIAL PIT INFILTRATION TEST RESULTS																		
water	level measurement No:	1	2	3	4	5	6	7	8	9	10	11	12	13	14 15	16	17	18	19
Soakage Trial 1	time [min] = depth to water [m] =		45 1.10																
Soakage Trial 2	time [min] = depth to water [m] =	Í	50 1.10																
Soakage Trial 3	time [min] = depth to water [m] =		65 1.10															_	

Spreadsheet provided by: www.YourSpreadsheets.co.uk

calculations are based on BRE Guidelines (Digest 365)