

Job Ref: 22-425

27/10/2022

Planning/Environmental Dept,  
South Dublin County Council,  
County Hall,  
Tallaght,  
Dublin

**Re: Surface Water Drainage Design for a Proposed Extension**

Applicant: Kevin & Aishling Doherty

Site Address: 46 Glendoher Drive, Rathfarnham, Dublin 16

To Whom it Concerns,

This is to state that Hydrocare Environmental Ltd. has been retained by the applicant to prepare a surface water drainage design for a proposed extension to an existing dwelling at 46 Glendoher Drive, Rathfarnham, Dublin 16. It is proposed to install a soakaway at the rear of the dwelling.

Due to lack of access at current it was not possible to carry out an infiltration test. The infiltration rate required for calculating the size and half-empty time for the soakaways was assumed based on past tests and experience in the area. However, it is proposed that an infiltration test be carried out prior to final construction in order to confirm and amend the size of the proposed soakaway as required.

Please see BRE 365 soakaway reports attached herewith.

We hope the above is to your satisfaction.

Yours sincerely,



Daniel Nolan, BA BAI, Msc Environmental Engineering, FETAC Site Assessor, MIEI

Tel: 0419842378 Mob: 0877905155 / 0872208633 Email: info@hydrocare.ie

Job Ref: 22-425

**Date:** 27 October 2022

**FAO:** McKevitt King Architects

**RE:** Soakaway Design per BRE 365

**Client:** Kevin & Aishling Doherty

**Location:** 46 Glendoher Drive, Rathfarnham, Dublin 16

---

Dear Emma Kennedy,

We have designed the soakaway per BRE 365 & C697 based on the total impermeable area outlined below, as provided by yourself, and Met Eireann's Extreme Rainfall Return Periods.

Site information supplied by:

McKevitt King Architects 50 North Road, Drogheda, Co. Louth

Total Impermeable Area: 49.00 m<sup>2</sup>

Rainfall Information as per Met Eireann:

Data for Kilmashogue, Dublin

30 year return period

Duration = 60 min

Rainfall Depth = 33.90 mm

Plus 20% climate change = 40.68 mm

The void ratio for the trench fill was set at 30% (0.3) to accommodate the use of granular fill material, i.e. Rounded gravel. The safety factor was taken as 1.

The total impermeable area is ca. 49 square metres and the runoff coefficient is to be set at 1.0 as per BRE 365.

<b>Inflow from:</b>			
	<b>Proposed impermeable areas:</b>	<b>Area (m<sup>2</sup>)</b>	<b>Runoff Volume (m<sup>3</sup>)</b>
1	Proposed Extension Roof	49	1.99332
2	-	0	0
3	-	0	0
4	-	0	0
	<b>Total inflow from:</b>	49.00	1.99332

The depth of the soakaway pit is set at 1.1m below the invert level of the drain. According to BRE 365 method, the pit was calculated as.

$$8.6 \text{ m L} \times 0.7 \text{ m W} \times 1.1 \text{ m D}$$

Storage required in soakaway (Inflow - Outflow):	1.93 m <sup>3</sup>
Capacity of pit required to accommodate fill material 30% void:	6.45 m <sup>3</sup>
Actual capacity of calculated soakaway:	6.62 m <sup>3</sup>

The soakaway shall be constructed in trenches as outlined below:

**2 no. trenches:**

**Trench No. 1                    4.3 m L x 0.7 m W x 1.1 m D**

**Volume: 3.311 m<sup>3</sup>**

**Trench No. 2                    4.3 m L x 0.7 m W x 1.1 m D**

**Volume: 3.311 m<sup>3</sup>**

**Total Volume of 6.622 m<sup>3</sup>**

NB

During the design process, a Silt Trap **must** be incorporated into any drains discharging into the soakaway system. All inflow from permeable paved areas must pass through a suitable geotextile to ensure filtration of fines.

NB

Any paved surface runoff or runoff from a Car parking area **must** pass through an oil interceptor \ hydrocarbon retention geotextile before discharge to the soakaway.

NB

Please note that for the purpose of this design, the fill material used must have no less free volume than 30%.

NB

*This design will comply with BRE 365's 24-hour maximum limit for Half-Empty time, with a half empty time of 16 hrs 28 mins*

NB

The base of the soakaway has **not** been included in the design calculations.

NB

All elements of the soakaway **must** be well maintained by suitable professionals, *i.e. Silt Traps must be regularly cleaned.*

NB

Please note that all relevant aspects of BRE365 **must** be taken into account in the design and installation of this Soakaway system, eg. Min. 5m separation distance from building foundations.

Hoping this is to your Satisfaction

Yours sincerely,



Daniel Nolan, BA BAI, Msc Environmental Engineering, FETAC Site Assesor

## Hydrocare Environmental Ltd. - BRE365 Design Calculations

CLIENT: **Kevin & Aishling Doherty**  
 LOCATION: **46 Glendoher Drive, Rathfarnham, Dublin 16**

<u>Inflow and Outflow</u>			
Impermeable Area [m <sup>2</sup> ]	49.00	Inflow =	49 x 0.04068 = 1.99332 m <sup>3</sup>
Rainfall Depth [mm]	40.68		
Soakaway No. 1 Length [m]	4.30	A <sub>s50 (1)</sub> =	( 4.3 x 0.55 x 2 ) + ( 0.7 x 0.55 x 2 ) = 5.5 m <sup>2</sup>
Soakaway Width [m]	0.70		
Soakaway Depth [m]	1.10	Outflow (1) =	5.5 x 0.0000015 x 3600 = 0.029333 m <sup>3</sup>
Storm Duration [min]	60		
Soakaway No. 2 Length [m]	4.30	A <sub>s50 (2)</sub> =	( 4.3 x 0.55 x 2 ) + ( 0.7 x 0.55 x 2 ) = 5.5 m <sup>2</sup>
Soakaway Width [m]	0.70		
Soakaway Depth [m]	1.10	Outflow (2) =	5.5 x 0.0000015 x 3600 = 0.029333 m <sup>3</sup>
Storm Duration [min]	60		
		A <sub>s50</sub> =	A <sub>s50 (1)</sub> + A <sub>s50 (2)</sub> = 11 m <sup>2</sup>
		Outflow =	11 x 0.0000015 x 3600 = 0.058667 m <sup>3</sup>
<u>Volume Required</u>			
Void Ratio [%]	30%	Storage =	1.99332 - 0.058667 = 1.93 m <sup>3</sup>
		Volume =	$\frac{1.9347}{0.3} = 6.45 \text{ m}^3$
<u>Half Empty Time</u>			
$T_{s50} = \frac{S \times 0.5}{A_{s50} \times f}$		=	$\frac{1.9347 \times 0.5}{11 \times 0.00000148 \times 3600} = 16.47 \text{ hrs}$
			= 16 hrs 28 mins

Met Eireann  
Return Period Rainfall Depths for sliding Durations  
Irish Grid: Easting: 313727, Northing: 225509,

DURATION	Interval		Years														
	6months,	1year,	2,	3,	4,	5,	10,	20,	30,	50,	75,	100,	150,	200,	250,	500,	
5 mins	2.7,	4.0,	4.6,	5.7,	6.4,	7.0,	8.9,	11.1,	12.5,	14.6,	16.5,	18.0,	20.3,	22.1,	23.6,	N/A	
10 mins	3.8,	5.5,	6.5,	7.9,	8.9,	9.7,	12.4,	15.4,	17.5,	20.4,	23.0,	25.1,	28.3,	30.8,	32.9,	N/A	
15 mins	4.4,	6.5,	7.6,	9.3,	10.5,	11.5,	14.5,	18.1,	20.5,	24.0,	27.1,	29.5,	33.3,	36.2,	38.7,	N/A	
30 mins	5.9,	8.5,	10.0,	12.2,	13.7,	14.9,	18.8,	23.3,	26.4,	30.7,	34.6,	37.6,	42.3,	46.0,	49.1,	N/A	
1 hours	7.7,	11.2,	13.0,	15.9,	17.8,	19.3,	24.3,	30.0,	33.9,	39.3,	44.2,	48.0,	53.9,	58.5,	62.3,	N/A	
2 hours	10.2,	14.6,	17.0,	20.7,	23.1,	25.1,	31.4,	38.7,	43.5,	50.3,	56.5,	61.2,	68.6,	74.4,	79.1,	N/A	
3 hours	12.0,	17.2,	19.9,	24.1,	27.0,	29.2,	36.5,	44.8,	50.4,	58.2,	65.2,	70.6,	79.0,	85.6,	91.0,	N/A	
4 hours	13.5,	19.2,	22.3,	26.9,	30.1,	32.5,	40.6,	49.8,	55.9,	64.5,	72.2,	78.1,	87.4,	94.6,	100.5,	N/A	
6 hours	15.9,	22.5,	26.1,	31.4,	35.1,	37.9,	47.2,	57.7,	64.7,	74.6,	83.3,	90.1,	100.7,	108.8,	115.6,	N/A	
9 hours	18.7,	26.4,	30.5,	36.7,	40.9,	44.2,	54.9,	67.0,	74.9,	86.2,	96.2,	104.0,	116.0,	125.3,	133.0,	N/A	
12 hours	21.0,	29.5,	34.1,	41.0,	45.6,	49.2,	61.0,	74.4,	83.2,	95.6,	106.6,	115.1,	128.3,	138.5,	146.9,	N/A	
18 hours	24.7,	34.6,	40.0,	47.9,	53.2,	57.4,	71.0,	86.3,	96.4,	110.5,	123.1,	132.8,	147.8,	159.4,	169.0,	N/A	
24 hours	27.8,	38.8,	44.7,	53.5,	59.4,	64.0,	79.0,	95.8,	107.0,	122.5,	136.3,	147.0,	163.5,	176.2,	186.7,	223.6	
2 days	35.1,	47.7,	54.4,	64.2,	70.7,	75.8,	92.0,	110.1,	121.8,	138.1,	152.4,	163.4,	180.2,	193.1,	203.8,	240.7	
3 days	41.0,	55.0,	62.2,	72.9,	79.9,	85.3,	102.6,	121.7,	134.0,	151.0,	165.9,	177.3,	194.6,	207.8,	218.7,	256.2	
4 days	46.2,	61.3,	69.0,	80.4,	87.9,	93.6,	111.9,	131.8,	144.7,	162.3,	177.7,	189.4,	207.2,	220.8,	232.0,	270.2	
6 days	55.3,	72.3,	81.0,	93.5,	101.8,	108.0,	127.9,	149.4,	163.1,	182.0,	198.3,	210.6,	229.3,	243.6,	255.2,	294.9	
8 days	63.4,	82.0,	91.4,	105.0,	113.9,	120.6,	141.9,	164.7,	179.2,	199.1,	216.1,	229.1,	248.6,	263.4,	275.5,	316.5	
10 days	70.9,	90.9,	101.0,	115.5,	124.9,	132.1,	154.5,	178.6,	193.8,	214.5,	232.3,	245.7,	266.0,	281.3,	293.8,	336.0	
12 days	77.8,	99.2,	109.9,	125.2,	135.2,	142.7,	166.2,	191.3,	207.2,	228.7,	247.2,	261.1,	282.0,	297.8,	310.6,	354.0	
16 days	90.8,	114.5,	126.3,	143.1,	154.0,	162.2,	187.7,	214.7,	231.7,	254.6,	274.2,	289.0,	311.1,	327.7,	341.2,	386.7	
20 days	102.9,	128.7,	141.5,	159.6,	171.2,	180.0,	207.2,	235.9,	253.9,	278.1,	298.8,	314.2,	337.4,	354.8,	368.8,	416.2	
25 days	117.1,	145.2,	159.1,	178.6,	191.2,	200.6,	229.8,	260.4,	279.5,	305.1,	326.9,	343.2,	367.5,	385.7,	400.5,	449.9	

NOTES:

N/A Data not available

These values are derived from a Depth Duration Frequency (DDF) Model


For details refer to:

'Fitzgerald D. L. (2007), Estimates of Point Rainfall Frequencies, Technical Note No. 61, Met Eireann, Dublin',

Available for download at [www.met.ie/climate/dataproducts/Estimation-of-Point-Rainfall-Frequencies\\_TN61.pdf](http://www.met.ie/climate/dataproducts/Estimation-of-Point-Rainfall-Frequencies_TN61.pdf)

FOR PLANNING PURPOSES ONLY  
NOT CONSTRUCTION ISSUE


2 No. SOAKAWAY 0.7m(W) x 4.3m(L) x 1.1m(D) – Refer to Hydrocare Environmental Ltd. BRE 365 design report for details.




42

44

48



ER DRIVE



**HYDROCARE**  
ENVIRONMENTAL LTD

Tel: 0419942378 / 0877905155  
E-mail: info@hydrocare.ie


SOAKAWAY LAYOUT

KEVIN & AISHLING DOHERTY  
46 GLENDOWER DRIVE,  
RATHFARNHAM


99/11/150 DATE: 27/10/2022

GLENDOWER PARK


**SOAKAWAY No.1  
LONG SECTION**




**SOAKAWAY No.2  
LONG SECTION**



**SOAKAWAY  
No.1 CROSS  
SECTION**



**SOAKAWAY  
No.2 CROSS  
SECTION**



**HYDROCARE**  
ENVIRONMENTAL LTD

Tel: 0419842378 / 0877905155  
E-mail: info@hydrocare.ie

SOAKAWAY SECTION

KEVIN & AISHLING DOHERTY  
46 GLENDOWER DRIVE  
RATHFARNHAM, DUBLIN 16

SCALE nts DATE: 27/10/2022