

D 01 Omos s59.2 seat or similar and approved scale @ 1:20
supplier: <http://omos.ie>

HC2089 CYCLE STAND RANGE

HC2089 Cycle Stand

HC2089 Cycle Stand Product Specifications:

- Stainless steel sheffield style cycle stand.
- 316 grade stainless steel.
- 1000x1000mm.
- Pipe is 50mm with a 2mm thickness.
- 750mm overground level and 250mm underground level.
- Brushed Finish.

Fittings: Root fixed underground level in concrete.

Concrete Foundations: Recommended concrete foundation 400x400x150mm per support.

Options Available:

- Base plates are available if required.
- Matches HC2061 or HC2062 Bollard.
- Other sizes also available.

D 02 Stainless steel Sheffield cycle stand or similar and approved
Supplier: <https://www.hartecast.com/all-products/cycle-stands/hc2089-sheffield-cycle-stand/>



D 03 Schwegler Bat Box or similar and approved

- * Height: 33cm
- * Diameter: 16cm
- * Weight: 4kg
- * Material: Schwegler Woodcrete
- * Colour: Black with grey front panel
- * Supplied with: Hanger and aluminium tree-friendly nail

supplier: <https://www.nhbs.com/title?slug=2f-schwegler-bat-box-general-purpose>

Cable Tie & Peg Example

Diagram 1: Lift top soil secure pin. Diagram 2: Top soil folded down to hide pin.

Labels: RubberGrass, 150mm, Top soil & grass, Pin, SOIL, unplug.

Legend: □ Peg Location, ○ Cable Tie Location

T: +44 (0)1794 513 184
E: sales@therubbercompany.com

Working With Companies Worldwide

D 04 Rubber grass mat safety surface or similar and approved
supplier: <http://therubbercompany.com>

gtRootbarrier 325

Introduction: gtRootBarrier 325 is manufactured using a unique coating to make it totally impermeable and is only available in the UK from Green-tech. Tree management means that the natural requirements of the tree are combined with the need to protect structures from the root system. We recommend that care is taken in laying the product and if in doubt consult a qualified arborist. Rootbarrier effectively controls the roots whilst protecting the tree roots from pollutants and acids in the soil. This helps the tree to establish quickly and keep it healthy, especially in the first five years of life.

Sizes:

Width	65cm	100cm	130cm	200cm
Roll Length	50m	50m	50m	50m
M ² /roll	32.5m ²	50m ²	65m ²	100m ²
Weight per roll	11kg	17kg	22kg	32kg

Technical Data:

Weight	325 gr/m ²	EN-ISO 9864
Puncture Resistance	3420 N	DIN 54307
Tensile Strength MD	22.8 kN/m	ISO 10319
Tensile Strength CMD	23.1 kN/m	ISO 10319
Tensile Strain at Max load MD	59.4 %	ISO 10319
Tensile Strain at max load CMD	41.3 %	ISO 10319
Tearing Strength MD	650.0 N	ASTM D 4533-1996
Tearing Strength CMD	607.0 N	ASTM D 4533-1996


The data are average values and indicative, based on the test report No. 1.125554/0198 (d.1-2010) of Institut für Textil- und Kunststofftechnik GmbH (IBU), Greven, Germany

Green-tech Ltd., Sweethills Park, Nunn Mankton, York, YO26 8ET
T: 01423 332 100 | sales@green-tech.co.uk | www.green-tech.co.uk

D 05 Root barrier or similar and approved
supplier: <http://green-tech.co.uk>



General Notes:



General Notes:



Project Name	Residential Development, Stoney Hill Road, Rathcoole	Drawing Name	Hard Landscape details 01
Status	Planning	Drawing No	LD-05-PP
Project No	18-008	Revision No	00
Scale	as shown	Drawn By	KG
Date	31.03.2023	Checked By	LD
Linda Doyle Director +353 (0)87 287 4196 info@doyle-otroithigh.com	Dathi O'Troithigh Director +353 (0)86 300 3490 dath@doyle-otroithigh.com	Office Address Penrose House 29-31 Upper Penrose St Dublin 2	Contact mail@doyle-otroithigh.com +353 (0)1 608 7762

General Notes: