

NOT FOR CONSTRUCTION

NOTES

- ALL DRAWINGS TO BE CHECKED BY CONTRACTOR ON SITE AND ENGINEER INFORMED OF DISCREPANCIES BEFORE WORK COMMENCES
- COMMENCES

 2. ALL LEVELS ARE IN METRES AND ARE RELATED TO ORDNANCE DATUM

 3. ALL DIMENSIONS TO BE IN MILLIMETERS UNLESS NOTED OTHERWISE

 4. CONTRACTOR SHALL SATISFY HIMSELF AS TO THE ACCURACY OF PAVEMENT LEVELS ON SITE PRIOR TO COMMENCEMENT OF WORKS ON SITE

 5. ALL SURFACE WATER DRAINAGE WORKS TO BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE LOCAL AUTHORITY'S CODE OF PRACTICE FOR DRAINAGE AND THE GDSDS

- GDSDS

 6. ALL SURFACE WATER SEWERS TO BE CLASS H CONCRETE TO EN1916 & IS 6 2004.

 7. ALL FOUL DRAINAGE WORKS TO BE IN ACCORDANCE WITH IRISH WATERS' CODE OF PRACTICE FOR WASTEWATER SUPPLY AND WASTEWATER INFRASTRUCTURE STANDARD DETAILS.

 8. FOUL SEWERS TO BE THERMOPLASTIC STRUCTURED WALL PIPES (COMPLYING WITH THE PROVISION OF IS EN 13476 AND WIS 4-35-01 2000) AND COMPLY WITH THE REQUIREMENTS OF THE IRISH WATER CODE OF PRACTICE

 9. WATERMAIN INSTALLATION AND ALL WATER SUPPLY WORKS TO BE IN ACCORDANCE WITH THE REQUIREMENTS OF IRISH WATER'S CODE OF PRACTICE FOR WATER SUPPLY AND WATER INFRASTRUCTURE STANDARD DETAILS

 10. WATERMAINS TO BE TYPE HPPE, PE-100, SDR-17 RATED AND SHALL CONFORM TO IS EN 12201 (PART 1, PART 2 & PART 3).
- PART 3).


 11. WATERMAIN SERVICE CONNECTION PIPES TO BE HDPE (PE-80)
 MATERIAL WITH SDR-17 RATING

 12. ANCHOR BLOCKS TO BE POSITIONED AT DEAD ENDS, TEES,
 BENDS AND AT EACH SIDE OF HYDRANTS AND VALVES IN
 ACCORDANCE WITH THE REQUIREMENTS OF IRISH WATER
 STANDARD DETAIL STD-W-28 (WATER MAIN THRUST AND
- STANDARD DETAIL STD-W-28 (WAIER MAIN THRUST AND SUPPORT BLOCKS.

 13. HYDRANT OUTLET TO BE 200mm BELOW GROUND LEVEL UNLESS REQUESTED OTHERWISE.

 14. WHERE COVER TO PIPE IS LESS THAN 900mm IN GREEN AREAS AND 1200mm IN TRAFFICKED AREAS, ENCASE PIPE IN NEW 150mm CONCRETE WITH MOVEMENT JOINTS.





4 Wheel Drive Car Overall Length Overall Width Overall Body Height
Min Body Ground Clearance
Max Track Width
Lock—to—lock time
Curb to Curb Turning Radius

COMPLIANCE



Scope House, 75 Shelton Street,
Perrystown, Covent Garden,
Dublin D12 K8PP London WC2H 9JQ
www.gdalyconsulting.com

U-Store-It - Liffey Valley

CLIENT

Parking Autotrack

scale: N/A

USLV-GDE-ZZ-DR-C-0012 P